

GEMSWAX SOLID



TECHNICAL DATA SHEET

PRODUCT DESCRIPTION

Pasty-looking wax suitable for polishing and protecting surfaces in marble and granite, agglomerate, natural stone. The components present in the wax provide the treated surfaces with an excellent shine along with a long life thanks to the strong penetration power and considerable resistance.

Thanks to these properties it is possible to eliminate defects due to small cracks or loss of gloss, obtaining a streak-free gloss.

APPLICATION

Spread small quantities of GemsWax Solid on the surface to be treated with circular movements using a cotton cloth making it penetrate as well as possible.

After waiting 30/60 minutes, pass by hand or with a machine, with a cotton cloth or fine iron wool or bristle brush until the desired shine is obtained.

HEALTH & SAFETY

Read Safety Data Sheet before handling or using this product.

STORAGE

If stored in dry and cool condition (5-25°C/41-77°F) in its closed original container at least 12 months from production. Use open containers as quick as possible.

IMPORTANT NOTICE

The above information is based on the latest stage of development and application technology. Due to a multiplicity of different influencing factors, this information, as well as other oral or written technical advises, must be considered as non-binding hints.

The user is obliged in each particular case to conduct performance tests, including but not limited to trails of the product, in an inconspicuous area or fabrication of a sample piece.