

GEMSEAL ACQUASTOP

PROTECTION OF CEMENTITIOUS RENDERS,
CELLULAR CONCRETE, FACING BRICKS,
INTERLOCK TILES, NATURAL AND ARTIFICIAL
STONE AGAINST RAIN & WEATHERING.



TECHNICAL DATA SHEET

PRODUCT DESCRIPTION

GEMSEAL ACQUASTOP is a Neutral water-based water proofing agent for protection of cementitious renders, cellular concrete, facing bricks, interlock tiles, natural and artificial stone with exceptional durability against diverse weather conditions and UV; for outdoor and indoor applications. The product doesn't make any film and it will not change the natural aspect of the surface.

APPLICATION

All surfaces to be treated must be completely clean and dry. Where no previous treatment experience exists a small discreet area should be tested to verify the suitability of the product to the stone. Apply one coat of ACQUASTOP evenly by spraying using a low pressure pump garden spray type unit or with a

roller or by cloth in circular movements. The most efficient method is by spraying. On very absorbent surfaces apply a second or third coat allowing sufficient time between each application (20-30 minutes) to penetrate into the stone and dry. If in doubt test discreet area to ensure second or third application is necessary.

In case of over treatment or any air bubbles remove by wiping excess product using a clean cotton cloth or absorbent paper. Temperature of surface to be treated should not be below 10°C. Avoid direct sunlight especially for external works.

PACKAGING

- 25 ltrs
- 60 ltrs
- 1000 ltrs

GEMSEAL ACQUASTOP

**PROTECTION OF CEMENTITIOUS RENDERS,
CELLULAR CONCRETE, FACING BRICKS,
INTERLOCK TILES, NATURAL AND ARTIFICIAL
STONE AGAINST RAIN & WEATHERING.**



DRYING TIME

Dry 2 to 3 hours, safe to walk on carefully. Fully effective within 48-72 hours before resuming normal use.

COVERAGE PER LT

Approximate coverage considering 1 coat: 4 - 6 sqm

WARRANTY

The technical advice whether verbal or in writing or by way of trials are given in good faith but without warranty. The application use or processing of the products are beyond our control and should be tested for their suitability and therefore your own responsibility. In no event shall GEMS ITALIA SRLS be liable to the customer or anyone

else for incidental or consequential damages, however occasioned. **ALWAYS TEST FIRST.**

STORAGE

Keep product in cool and dry surroundings.

IMPORTANT SAFETY NOTE

When using any type of product suitable ventilation should be provided during and after application. Use appropriate rubber gloves where necessary and do not smoke, eat or drink while using product. Keep product well closed and out of the reach from children. Additional information available on Material Safety Data Sheet.