

# GEMSKID G

ANTI-SLIP TREATMENT OF **NON-LIMESTONE** SURFACES AND AGGLOMERATES OF QUARTZ AND RESIN



## TECHNICAL DATA SHEET

### PRODUCT DESCRIPTION

It is a mixture of acids and surfactants indicated for the anti-slip treatment of non-limestone surfaces and agglomerates of quartz and resin.

### APPLICATION

The method of use and dilution varies according to the type of surface. Application by brush, spray with low pressure pump or roller is recommended. Leave the product to act for 5 minutes. The rinse with water and repeat the operation if necessary until the desired results is completely obtained. Use gloves and a mask during use.

### HEALTH & SAFETY

As with all chemical substances, the rule of operating in safety and wearing personal protective equipment (PPE) where applicable applies. Before use, consult the safety data sheet.

### STORAGE

The product is stable for 12 months from the date of receipt if kept in the original packaging and stored at a temperature between +5 and +25°C.

### COVERAGE

Lt 1 = 5 sqm - Use the product pure  
Lt 1 = 10 sqm - Dilution for hard surface 1/1  
Lt 1 = 15 sqm - Dilution for medium hard surface 1/2  
Lt 1 = 20 sqm - Dilution for soft surface 1/1.

### LIMITATION OF LIABILITY

This information is based on our knowledge and experience. Due to the diversity of materials on the market, the suitability of the product for the specific use taken into consideration must be verified with adequate tests.

The responsibility of Gems S.r.l.s. is limited to guaranteeing the constant quality of the product.